



MODELLO / Model	POTENZA UTILE MAX/ Putere utila maxima		POTENZA MAX FOC./ Putere maxima focar		ATTACCHI / Racorduri			CAPACITA' / Capacitate apa
	Kcal/h	Kw	Kcal/h	Kw	MANDATA /	RITORNO /	Uscita fumi / Iesire fum mm	Lt
					Tur ISO 7/1	Retur ISO 7/1		
ECOGEN 20	17.200	20	18.900	22	Ø 1 1/4"	Ø 1 1/4"	Ø 150	55
ECOGEN 30	25.800	30	28.400	33	Ø 1 1/4"	Ø 1 1/4"	Ø 150	70
ECOGEN 40	34.400	40	41.500	48	Ø 1 1/2"	Ø 1 1/2"	Ø 150	90
ECOGEN 50	43.000	50	52.000	60	Ø 1 1/2"	Ø 1 1/2"	Ø 150	110
ECOGEN 70	60.200	70	69.600	81	Ø 2"	Ø 2"	Ø 180	150
ECOGEN 90	77.400	90	88.000	102	Ø 2"	Ø 2"	Ø 180	190
ECOGEN 120	102.000	118	112.000	130	Ø 2"	Ø 2"	Ø 200	250
ECOGEN 150	129.500	150	146.000	170	Ø 2"	Ø 2"	Ø 200	310

MODELLO / Model	DIMENSIONI / Dimensiuni mm							ALTEZZA ATTACCHI / Inaltime racorduri mm			PESO / Greutate KG		
	A	B1	B2	B3	C	Buncar	D	E	F	F1		F2	F3
ECOGEN 20	550	1200	160	1040	1500	40 Kg	150	1100	220	860	715	220	200
ECOGEN 30	550	1200	160	1040	1500	50 Kg	150	1240	230	860	715	220	250
ECOGEN 40	650	1300	160	1140	1600	75 Kg	150	1240	230	960	815	240	330
ECOGEN 50	650	1300	160	1140	1600	90 Kg	150	1360	230	960	815	240	400
ECOGEN 70	750	1400	160	1240	---	---	150	1360	250	1060	915	260	510
ECOGEN 90	750	1400	160	1240	---	---	170	1560	250	1060	915	260	600
ECOGEN 120	850	1500	160	1340	---	---	170	1560	300	1060	1015	280	700
ECOGEN 150	950	1600	160	1440	---	---	170	1600	300	1260	1150	300	880

CONTENITORE AFFIANCATO / Buncar combustibil latera	LARGHEZZA / Lungime mm	PROFONDITA' / Adancime mm	ALTEZZA / Inaltime mm	CAPACITA' / Capacite KG
STANDARD	300	800	1200	130
MEDIU (Optional)	450	900	1500	240
MARE (Optional)	600	900	1500	400